



VALVES FOR PLUMBING AND GAS SYSTEMS, 100% MADE IN ITALY

HYDRO COMPONENTS | CENTRAL HEATING | RADIANT SYSTEMS | FAUCETS



TIEMME RACCORDERIE S.p.A.

Via Cavallera, n. 6/A - 25045 Castegnato (BS) - Italy
Tel. +39 030 2142211
info@tiemme.com

customerservice@tiemme.com

www.tiemme.com





2380
2330
Female/female ball valves with steel flat handle

Code	Size	PN	MRP in Rs.	Unit/Box
231 0051	1/4" ISO7	50	530	25/100
231 0049	3/8" ISO7	50	530	25/100
236 0017	1/2"	40	490	25/100
236 0016	3/4"	30	740	15/60
236 0013	1"	30	1160	12/48
236 0021	1" 1/4	25	1910	8/32
236 0027	1" 1/2	25	2730	4/16
236 0018	2"	25	4470	2/8
231 0047	2" 1/2	18	12330	1/4
231 0040	3"	16	17530	1/3
231 0050	4"	16	29630	1/1



3506
Female/female ISO 228 check valve EUROSTOP with metallic shutter



Code	Size	PN	MRP in Rs.	Unit/Box
350 0142	1/2"	25	740	15/60
350 0143	3/4"	25	980	10/40
350 0144	1"	25	1310	6/24
350 0145	1" 1/4	18	2030	5/20
350 0146	1" 1/2	18	2790	2/8
350 0147	2"	18	4270	2/8
350 0050	2" 1/2	12	10400	1/6
350 0051	3"	12	15630	1/4
350 0058	4"	12	25920	1/2



1900
Automatic air vent valve

Code	Size	Ø	MRP in Rs.	Unit/Box
198 0002	3/8"	39	670	1/50
198 0001	1/2"	39	710	1/50
198 0013	3/4"	45,5	1190	1/25
198 0022	1"	45,5	1380	1/25



2380G07
Gas female/female ISO7/EN 10226 ball valves with yellow steel flat handle

Code	Size	MRP in Rs.	Unit/Box
239 0001	1/2"	600	20/80
239 0006	3/4"	900	14/56
239 0007	1"	1450	10/40
239 0004	1" 1/4	2220	6/24
239 0002	1" 1/2	3240	3/12
239 0005	2"	5330	2/8



3500
Female/female ISO 228 check valve YACHT with polyamide shutter



Code	Size	PN	MRP in Rs.	Unit/Box
350 0003	1/2"	12	520	15/60
350 0004	3/4"	12	710	12/48
350 0001	1"	12	940	8/32
350 0006	1" 1/4	10	1350	6/24
350 0008	1" 1/2	10	2030	4/16
350 0007	2"	10	2790	2/8
350 0022	2" 1/2	8	5330	1/6
350 0018	3"	8	7520	1/4
350 0034	4"	8	13100	1/2



4737
Chrome-plated female thermostatic adjustable mixing valve for domestic hot water

TECHNICAL CHARACTERISTICS

- Compliance with: UNI EN 1111
- Range of temperature (°C): 30÷55°C
- Max operating pressure: 10 bar
- Max operating temperature: 90°C
- Material: brass CW617N
- Setting knob: PA
- Flow rate to 3 bar: 30 l/min

Code	Size	MRP in Rs.	Unit/Box
320 0038	1/2"	5900	1/10
320 0037	3/4"	5900	1/10



3110N
Piston pressure reducing valve F/F connections

TECHNICAL CHARACTERISTICS

- Setting range: 1-6 bar (Factory setting 3 bar)
- Max inlet pressure: 25 bar
- Max operating temperature : 80°C
- Body: nickel-plated CW617N brass
- Threads: Female ISO 228
- Pressure gauge connection: 1/4"F

Code	Size	MRP in Rs.	Unit/Box
318 0008	1/2"	3190	1/10
318 0010	3/4"	4540	1/10
318 0003	1"	5490	1/8
318 0012	1" 1/4	9160	1/8
318 0014	1" 1/2	11980	1/8
318 0009	2"	14130	1/8
318 0016	2" 1/2	27620	1/2
318 0015	3"	40430	1/1
318 0006	4"	100420	1/1



3670
Y strainer

TECHNICAL CHARACTERISTICS:

- Performance: from 350 µm to 600 µm according to the diameter
- Body: CW 617N brass
- Max operating pressure: 20 bar up to 2"; 16 bar over 2"
- Max operating temperature: 100°C
- Threads: female/female ISO 228


Code	Size	MRP in Rs.	Unit/Box
367 0003	1/2"	620	20/80
367 0001	3/4"	1050	18/54
367 0002	1"	1790	10/30
367 0005	1" 1/4	2530	4/16
367 0009	1" 1/2	3730	3/12
367 0004	2"	5770	2/8
367 0011	2" 1/2	12630	1/8
367 0014	3"	19070	1/5
367 0015	4"	36840	1/1

With holes for applying a lead seal



0480CR
Shattaf shower chrome with Chrome Stainless Steel pipe. Chrome brass connections.

Code	Series	MRP in Rs.	Unit/Box
048 0012	NETTUNO COLLECTION	1990	1/48



3100N
Piston pressure reducing valve F/F connections

TECHNICAL CHARACTERISTICS

- Setting range: 1-4 bar (Factory setting 3 bar)
- Max inlet pressure: 15 bar
- Max operating temperature : 80°C
- Body: nickel-plated CW617N brass
- Threads: Female ISO 228
- Pressure gauge connection: 1/4"F

Code	Size	MRP in Rs.	Unit/Box
318 0057	1/2"	2030	1/25
318 0058	3/4"	2130	1/25



3180
Diaphragm pressure reducing valve F/F connections

TECHNICAL CHARACTERISTICS


- Setting range: 1-6 bar (Factory setting 3 bar)
- Max inlet pressure: 16 bar
- Max operating temperature : 65°C
- Body: nickel-plated CW617N brass
- Threads: Female ISO 7/EN 10226
- Pressure gauge connection: 1/4"F

Code	Size	MRP in Rs.	Unit/Box
318 0017	1/2"	3600	1/10
318 0013	3/4"	3980	1/10



3906C
Chrome-plated angle valve with rosette

Code	Size	MRP in Rs.	Unit/Box
295 0132	1/2" x 3/8"	510	1/60
295 0130	1/2" x 1/2"	520	1/60



2530
Bibcock with red plasticized steel flat handle and hose connection

Code	Size	MRP in Rs.	Unit/Box
250 0006	1/2"	1020	12/48
250 0008	3/4"	1370	7/28
250 0015	1"	2470	4/16